

MATERIAL SAFETY DATA SHEET
OSHA FORM 174

PRODUCT NAME: WINSOL AWNING CLEANER & PROTECTANT
PRODUCT CODE: 2050

HMIS CODES: H - 1 F - 0 R - 0 P - B

(HEALTH - FIRE - REACTIVITY - PERSONAL PROTECTION)

HMIS RATING: 0=MINIMAL, 1=SLIGHT, 2=MODERATE, 3=SERIOUS,
4=SEVERE

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: WINSOL LABORATORIES, INC.

ADDRESS: 1417 NW 51ST, SEATTLE, WA., 98107

EMERGENCY PHONE: 206/782-5500

DATE PREPARED: 4-01-89 NAME OF PREPARER: WINSOL
LABORATORIES, INC.

REVISED: 01-01-09

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS VAPOR COMPONENTS PRESS	CAS # WEIGHT %	OSHA PEL	ACGIH TLV	OTHER
-------------------------------------------	----------------------	-------------	--------------	-------

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

SARA TITLE III / SECTION 313 SUPPLIER NOTIFICATION

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE
EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF
1986 AND OF 40 CFR 372:

CAS: #	CHEMICAL NAME	PERCENT BY WEIGHT
NONE		

BOILING POINT: N.A.

SPECIFIC GRAVITY (H2O=1):>1

VAPOR DENSITY: N.A.

EVAPORATION RATE:<1

V.O.C.: N.A.

(ETHER=1)

SOLUBILITY IN WATER: 100%
APPEARANCE AND ODOR: TRANSLUCENT, NONE

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

WINSOL AWNING CLEANER & PROTECTANT IS CONSIDERED NON-FLAMMABLE

FLASH POINT: N.A.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: NA UPPER:NA

EXTINGUISHING MEDIA: WATER

SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN A PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: STRONG OXIDIZING AGENTS, ACIDS

INCOMPATIBILITY (MATERIALS TO AVOID): NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

EYE MAY CAUSE EYE IRRITATION.

SKIN PROLONGED OR REPEATED AND CONFINED EXPOSURE MAY CAUSE SKIN IRRITATION. REPEATED CONTACT MAY CAUSE DRYING OR FLAKING OF SKIN.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: A SINGLE PROLONGED EXPOSURE IS NOT LIKELY TO RESULT IN THE MATERIAL BEING ABSORBED THROUGH THE SKIN IN A HARMFUL AMOUNT. THE DERMAL LD50 HAS NOT BEEN DETERMINED.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, AND DIARRHEA.

SECTION VI - HEALTH HAZARD DATA - CONT.

CARCINOGENICITY: THIS MATERIAL IS NOT CONSIDERED TO BE A CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM, THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER, OR THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION.

NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

EMERGENCY AND FIRST AID PROCEDURES:

EYES IRRIGATE WITH FLOWING WATER IMMEDIATELY AND CONTINUOUSLY FOR 15 MINUTES. CONSULT MEDICAL PERSONNEL.

SKIN WASH OFF IN FLOWING WATER OR SHOWER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

INGESTION DO NOT INDUCE VOMITING. CALL PHYSICIAN

INHALATION REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL- ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL AND TRANSFER TO LABELED CONTAINERS.

LARGE SPILL- STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID INTO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND , CLAY, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO LABELED CONTAINERS.

WASTE DISPOSAL METHOD: REVIEW FEDERAL, PROVINCIAL AND LOCAL GOVERNMENT REQUIREMENTS PRIOR TO DISPOSAL

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: EXERCISE REASONABLE CARE AND CAUTION. STORE IN A COOL PLACE.

OTHER PRECAUTIONS: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID AND/OR SOLIDS), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: IF TVL OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITION.

VENTILATION: PROVIDE GENERAL OR MECHANICAL VENTILATION OR

LOCAL EXHAUST TO KEEP VAPOR CONCENTRATIONS BELOW TLV OF MATERIALS IN SECTION II AND LEL IN SECTION IV.

PROTECTIVE GLOVES: USE IMPERMEABLE GLOVES TO PREVENT PROLONGED SKIN CONTACT.

EYE PROTECTION: USE SAFETY EYE-WEAR DESIGNED TO PROTECT EYES AGAINST LIQUID SPLASH AND MISTS. CONSULT YOUR SAFETY EQUIPMENT SUPPLIER.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: USE PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. USE HEAD CAPS, BOOTS, CHEMICAL APRONS WHEN NECESSARY

WORK/HYGIENIC PRACTICES: EYE WASHES AND SAFETY SHOWERS IN THE WORK-PLACE ARE RECOMMENDED. WASH HANDS AFTER USING. MONITOR EXPOSURE LEVELS.

SECTION IX - DISCLAIMER

NOTICE: ALTHOUGH THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN (HEREINAFTER "INFORMATION") ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THE DATE HEREOF, WINSOL LABORATORIES, INC. MAKES NO REPRESENTATIONS AS TO THE COMPLETENESS OR ACCURACY THEREOF. INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING SAME WILL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY FOR THEIR PURPOSES PRIOR TO USE. IN NO EVENT WILL WINSOL LABORATORIES, INC. BE RESPONSIBLE FOR DAMAGES OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

TLV IS A REGISTERED TRADEMARK OF THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH)

REVISED:

01-01-09 – UPDATE

